

vStack-R

vStack-R-SL201- D12RE-G3



2U rack server



Front View of 2U 8-bay Model



Rear View of 10 PCIe Slots



Front View of 2U 12-bay Model



Rear View of Rear 2.5inch Module



Front View of 2U 25-bay Model



Rear View Rear 3.5inch Module

PRODUCT OVERVIEW

vStack-R 2U dual-socket high-end server adopts vStack-R G4DCL-B motherboard, supports 1 or 2 third-generation Intel® Xeon® Scalable processors, 32 DIMM DDR4 memory slots, on-board 2 M.2 interfaces, 2 Gigabit Ethernet ports, 1 RJ45 management network port, 11 PCIe3.0/PCIe4.0 expansion slots, suitable for virtualization, cloud computing, big data processing, high-performance computing, distributed storage, enterprise market and telecom applications and other needs.

- 01 1 or 2 Gen3 Intel® Xeon® Scalable, up to 270W TDP

- 02 Up to 32 DDR4 slots, frequency 2666/2933/3200 MHz

- 03 2 built-in NVMe PCIe 4.0 M.2 interfaces

- 04 Various combinations of PCIe and hard drives

- 05 Up to 11 PCIe expansions, optional support for 2 double-width, full-height, full-length GPUs

REMOTE CONTROL

All vStack-R servers are equipped with an integrated Baseboard Management Controller (BMC) that supports Remote Management and Monitoring IPMI 2.0.

The operation of BMC does not depend on the operating system of the server and provides the following features through a dedicated 1Gb RJ45 port:

Configure server hardware settings, including BIOS and hardware RAID	▼
Real-time system status monitoring	▼
KVM over IP - remote access to the server's graphical console	▼
Virtual Media - remote connection of virtual media (CD / DVD images) to the server	▼
Power management: turn on, turn off, reboot	▼
Display of indications of temperature sensors	▼
Secure access via SSL	▼
Multi-user access, including integration with Active Directory	▼

Host Online

Quick Link...

- Dashboard
- Sensor
- System Inventory
- FRU Information
- Logs & Reports
- Settings
- Remote Control
- Image Redirection
- Maintenance
- Sign out

System Inventory System Inventory Information

Home > System Inventory

System Inventory Information

- Click on a component to view its detailed information.
- This page only show the component of CPU, DIMM and PCIE.

Block Diagram Layout View

Legend:

- CPU
- Active DIMM/PCI Slots
- Inactive DIMM/PCI Slots

The diagram illustrates the system architecture with two CPUs, CPU_0 and CPU_1. CPU_0 is connected to Channel_A through Channel_F. Channel_A is connected to RISER1 X16/X8 SLOT1 and RISER1 X8 SLOT3. Channel_B is connected to OCP 3.0. Channel_C is connected to RISER1 X8 SLOT2. Channel_D is connected to RISER2 X8 SLOT3. Channel_E and Channel_F are connected to PCI E PCH M.2 1 and PCI E PCH M.2 2 respectively. CPU_1 is connected to Channel_A through Channel_F. Channel_A is connected to RISER3 SLOT2. Channel_B is connected to RISER3 SLOT1. Channel_C is connected to RISER2 X16/X8 SLOT1. Channel_D is connected to RISER2 X8 SLOT2. Channel_E and Channel_F are connected to PCI Express Slim 1 and PCI Express Slim 2 respectively. Active DIMM/PCI Slots are shown in green, and inactive ones are in grey.

Host Online

Quick Link...

- Dashboard
- Sensor
- System Inventory
- FRU Information
- Logs & Reports
- Settings
- Remote Control
- Image Redirection
- Maintenance
- Sign out

Dashboard Control Panel

Home > Dashboard

5 d 9 hrs
HOST Running Time Since Last BMC FW Upgrade

16
Pending Deassertions

2
Access Logs

Firmware Information

BMC Firmware Revision
1.18.010000

BMC Firmware Build Time
Apr 22 2022 15:24:19 CST

BIOS Revision
801

BIOS Name
G3DCL

BIOS Firmware Build Time
12/19/2022 09:41:05

CPLD Revision
15

CPLD Name
G3DCL

CPLD Build Time
12/10/2020

Network Information

Host System

System LAN MAC Address1
00:24:ecf3:6a:1a

System LAN MAC Address2
00:24:ecf3:6a:1b

System LAN MAC Address3
00:24:ecf4:a0:b4

System LAN MAC Address4
00:24:ecf4:a0:b5

BMC Network Interface
Aggregated Network Interface

00:24:EC:F4:A0:B2

IPv4 Network Mode
Static

IPv4 Address
10.71.17.31

Sensor Monitoring

All sensors are good now!

Currently recovered




Product series	SL201-D08R-G3 SL201-D08R-NV-G3	SL201-D12R-G3 SL201-D12RE-G3 SL201-D12R-NV-G3	SL201-D25RE-G3
Product type	2U 8 bays	2U 12 bays	2U 25 bays
System size	748*433.4*87.6mm (D*W*H)		
Processor	Support 1 or 2 Gen3 Intel® Xeon® Scalable processors, TDP up to 270W		
Memory	32 DDR4 memory slots, support DDR4 LRDIMM/RDIMM 2666/2933/3200MHz		
Internal storage interface	3 Minis SAS HD interfaces, 2 SATA DOM interfaces, 2 NVMe PCIe 4.0 M.2 interfaces (size 2280)		
External hard drive	Front 8 hot-swap 3.5/2.5inch SAS/SATA/NVMe hard drives; Rear optional up to 2*2×3.5inch hard drive modules or 2*2×2.5 inch hard drive modules	Front 12 hot-swap 3.5/2.5inch SAS/SATA/NVMe drives; Rear optional 2* 2×3.5inch hard drive modules or 2*2×2.5inch hard drive modules	Front 25* hot-swap 2.5-inch SAS/SATA hard drives; Rear optional 2* 2×3.5inch hard drive modules or 2*2×2.5inch hard drive modules
External port	Front port: 1 VGA, 2 USB3.0		
External port	Rear port: 1 VGA, 1 COM port, 2USB3.0, 1 RJ45 Gigabit management network port, 2 Gigabit RJ45 network ports		
PCIe expansion form	6 PCIe full-height slots, 4* PCIe half-height slots, 1* OCP 3.0 slot		
*PCIe expansion specification	Riser 1: 1*full-height PCIe 4.0 x16, 2*full-height PCIe 4.0 x8, 2*full-height PCIe 4.0 x16 Riser 2: 1*full-height PCIe 4.0 x16, 2*full-height PCIe 4.0 x8, 2*full-height PCIe 4.0 x16 Riser 3: 1*half-height PCIe 4.0 x16, 1*half-height PCIe 3.0 x8, 1*half-height PCIe 3.0 x8 (in x16 Slot) Riser 4: 1*half-height PCIe 3.0 x8, 1*half-height PCIe 3.0 x8 (in x16 Slot) OCP: 1*OCP 3.0 (PCIe 3.0 x8)		
Safety	Optional TPM module		
Power supply	AC 220V 550W, 800W, 1300W, 1600W, 2000W, 2200W redundant power supply (adapt according to the actual power)		
Fan	Standard 4* 8038 hot-swap N+1 redundant fans, optional 8056 hot-swap N+1 redundant fans		
IPMI	IPMI2.0		

PRODUCT PARAMETERS

Product series	SL201-D08R-G3 SL201-D08R-NV-G3	SL201-D12R-G3 SL201-D12RE-G3 SL201-D12R-NV-G3	SL201-D25RE-G3
Management port	1 dedicated RJ45 management network port		
Certification	CCC, CE, FCC, ROHS		
Operating temperature & humidity	Temperature: 5°C~35°C Humidity: 20%~80% RH non-condensing		
Storage temperature & humidity	Short-time storage ($\leq 72\text{H}$): temperature -40°C~70°C/ humidity 20%~90% RH non-condensing (including packaging) Long-time storage ($> 72\text{H}$): temperature 20°C~28°C/ humidity 30%~70% RH non-condensing (including packaging)		

ORDERING INFORMATION

Model	Description
vStack-R SL201-D08R-G3	Dual-socket Whitley platform 2U 8-bay model, SATA/SAS direct connection version, standard 550W 1+1 redundant power supply
vStack-R SL201-D08R-NV-G3	Dual-socket Whitley platform 2U 8-bay model, SATA/SAS/NVMe direct connection version, standard 550W 1+1 redundant power supply
vStack-R SL201-D12R-G3	Dual-socket Whitley platform 2U 12-bay model, SATA/SAS direct connection version, standard 550W 1+1 redundant power supply
vStack-R SL201-D12R-NV-G3	Dual-socket Whitley platform 2U 12-bay model, SATA/SAS/NVMe direct connection version, standard 550W 1+1 redundant power supply
vStack-R SL201-D12R E-G3	Dual-socket Whitley platform 2U 12-bay model, SATA/SAS extended version, standard 550W 1+1 redundant power supply
vStack-R SL201-D25R E-G3	Dual-socket Whitley platform 2U 25-bay model, SATA/SAS extended version, standard 550W 1+1 redundant power supply

Main options	
Remote technical support Customer may contact by web on a 24/7/365 basis to report an issue.	
Second Line Support 10 a.m. to 18 p.m. (UTC+3), Monday through Friday.	
Replacement parts delivery Delivers within the Next business day.	
Software support Provides access to all patches and software upgrades	